



Model	Range (mm)	Accuracy (mm)	Resolution (mm/inch)	f (mm)
5106-15	± 15	± 0.02	0.01/0.0005"	21
5106-20	± 20	± 0.02	0.01/0.0005"	25

- Response speed: 3m/s
- Automatic power off in 5 minutes
- Absolute and relative measurements are available
- Operating Temperature 0 ~ 40°C
- Humidity $\leq$ 80% RH
- Battery 3V CR2032 environmental lithium battery

- Response speed: 3m/s
- Automatic power off in 5 minutes
- Absolute and relative measurements are available
- Operating Temperature 0 ~ 40°C
- Humidity $\leq$ 80% RH
- Battery 3V CR2032 environmental lithium battery



Model	Range (mm)	Accuracy (mm)	Resolution (mm/inch)	L (mm)
5114-25	0-25	± 0.02	0.01/0.0005"	114
5114-50	0-50	± 0.02	0.01/0.0005"	140

Model	Range (mm)	Accuracy (mm)	Resolution (mm/inch)	L (mm)
5114-25	0-25	± 0.02	0.01/0.0005"	114
5114-50	0-50	± 0.02	0.01/0.0005"	140

- Measure the depth of narrow grooves and holes
- Material: Stainless steel
- Battery: 3V CR2032 environmental lithium battery
- Buttons: on/off, zero, mm/inch conversion
- Waterproof level: IP54
- Automatic power on/off

- Measure the depth of narrow grooves and holes
- Material: Stainless steel
- Battery: 3V CR2032 environmental lithium battery
- Buttons: on/off, zero, mm/inch conversion
- Waterproof level: IP54
- Automatic power on/off